

## **Certificate of Conformity**

Certificate Number: CN-PV-200142

On the basis of the tests undertaken, the samples of the below product have been found to comply with the requirements of the referenced specifications /standards at the time the tests were carried out. It does not imply that Intertek has performed any surveillance or control of the manufacture. The manufacturer shall ensure that the manufacturing process assures compliance of the production units with the examined products mentioned in this certificate.

Applicant Name & Address: Shenzhen Growatt New Energy Co., Ltd

2F and 3F, Building 4, Jiayu Company Industrial Park, Xibianling, Shangyu

Village, Shiyan Street, Bao'an District, Shenzhen, China

Product Description: PV Grid inverter

Ratings & Principle Characteristics:

inciple See Annex to Certificate of Conformity

Models/Type References:

MIC 600TL-X, MIC 750TL-X, MIC 1000TL-X, MIC1500 TL-X, MIC 2000TL-X,

MIC 2500TL-X, MIC 3000TL-X, MIC 3300TL-X

Brand Name: Growatt

Specification/Standard: IEC/EN 62109-1:2010 (First Edition) Safety of Power Converter for use in

Photovoltaic Power Systems Part 1: General requirements

IEC/EN 62109-2:2011 Safety of Power Converter for use in Photovoltaic

Power Systems Part 2: Particular requirements for inverters

Certificate Issuing Office Name Interte

& Address:

Intertek Testing Services Ltd. Shanghai

West Area, 2nd Floor, No. 707, Zhangyang Road China (Shanghai) Pilot

Free Trade Zone, Shanghai, P. R. China

Test Report Number: 200903138GZU-001, 200903138GZU-002

Additional information in Appendix.

Signature

**Certification Manager: Grady Ye** 

/ susta

Date: 29 October 2020

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



## **APPENDIX: Certificate of Conformity**

This is an Appendix to Certificate of Conformity Number: CN-PV-200142

Ratings & Principle Characteristics:

Model	MIC 600TL-X	MIC 750TL-	MIC 1000TL-X	MIC 1500TL-X	
Max.PV voltage	500Vdc				
PV voltage range	50V – 500Vdc				
Max.input current	13A				
PV Isc	16A				
Nominal output voltage	230Vac				
Nominal output Frequency	50/60Hz				
Max.output current	2.9A	3.6A	4.8A	7.1A	
Max.output power	600W	750 W	1000 W	1500 W	
Max.apparent power	600VA	750 VA	1000 VA	1500 VA	
Power factor range	0.8Leading – 0.8 lagging				
Safety level	Class I				
Ingress Protection	IP 65				
Operation Ambient Temperature	<b>-25</b> ℃ - +60℃				
Software Version	GH1.0				

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



## **APPENDIX: Certificate of Conformity**

This is an Appendix to Certificate of Conformity Number: CN-PV-200142

Ratings & Principle Characteristics:

	Model	MIC 2000TL-X	MIC 2500TL-X	MIC 3000TL-X	MIC 3300TL-X	
	Max.PV voltage	500Vdc	550Vdc			
	PV voltage range	50V – 500Vdc	65V – 550Vdc			
	Max.input current	13A				
	PV Isc	16A				
	Nominal output voltage	230Vac				
	Nominal output Frequency	50/60Hz				
	Max.output current	9.5A	11.9A	14.3A		
	Max.output power	2000 W	2500 W	3000 W	3300 W	
	Max.apparent power	2000 VA	2500 VA	3000 VA	3300 VA	
	Power factor range	0.8Leading – 0.8 lagging				
	Safety level	Class I				
	Ingress Protection	IP 65				
	Operation Ambient Temperature	-25℃ - +60℃				
	Software version	GH1.0				

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.